



[Alauda Container Platform](#) > [API References](#) > [Advanced APIs](#) > Cluster APIs

Cluster APIs

Cluster [v1]

/auth/v1/clusters

`get` list clusters by rbac

Parameters

- `Authorization` (*in header*): `string`
Given Bearer token will use this as authorization for the API
- `labelSelector` (*in query*): `string`
A selector to restrict the list of returned objects by their labels.
- `fieldSelector` (*in query*): `string`
A selector to restrict the list of returned objects by their fields.
- `limit` (*in query*): `integer`
limit the number of returned records.
- `continue` (*in query*): `string`
continue token for paginated queries.
- `resourceVersion` (*in query*): `string`
resourceVersion sets a constraint on what resource versions a request may be served from.
- `watch` (*in query*): `boolean`
watch for changes to the described resources.
- `timeoutSeconds` (*in query*): `integer`

timeoutSeconds for the list/watch call.

Response

- `200` [ClusterList](#): OK
- `401` : Unauthorized - Invalid or missing authentication credentials

ClusterList

ClusterList is a list of Cluster resources.

- `apiVersion` : `string`
- `kind` : `string`
- `metadata` : [ListMeta](#)
- `items` : `[]`[Cluster](#)

ListMeta

- `continue` : `string`
- `remainingItemCount` : `integer`
- `resourceVersion` : `string`
- `selfLink` : `string`

Cluster

Cluster contains information about a cluster in a cluster registry.

- `apiVersion` : `string`
APIVersion defines the versioned schema of this representation of an object.
- `kind` : `string`
Kind is a string value representing the REST resource this object represents.

- `metadata` : [ObjectMeta](#) ↗

ObjectMeta is metadata that all persisted resources must have, which includes all objects users must create.

- `spec` : [ClusterSpec](#)

Spec is the specification of the cluster.

- `status` : [ClusterStatus](#)

Status is the status of the cluster.

ClusterSpec

Spec is the specification of the cluster.

- `authInfo` : [ClusterAuthInfo](#)
- `kubernetesApiEndpoints` : [KubernetesAPIEndpoints](#)

ClusterAuthInfo

- `controller` : [ClusterAuthReference](#)
- `user` : [ClusterAuthReference](#)

ClusterAuthReference

- `kind` : `string`
- `name` : `string`
- `namespace` : `string`

KubernetesAPIEndpoints

- `caBundle` : `string`

CABundle contains the certificate authority information.

- `serverEndpoints` : `[]ServerAddressByClientCIDR`

ServerEndpoints specifies API server addresses for clients.

ServerAddressByClientCIDR

- `clientCIDR` : `string`

CIDR used by clients to match the corresponding server address.

- `serverAddress` : `string`

Server address suitable for a client in the matching CIDR.

ClusterStatus

Status is the status of the cluster.

- `conditions` : `[]ClusterCondition`

Conditions contains the different condition statuses for this cluster.

- `type` : `string`

Type contains the type of this cluster.

- `version` : `string`

Version contains the kubernetes version for this cluster.

ClusterCondition

ClusterCondition contains condition information for a cluster.

- `lastHeartbeatTime` : `string`

LastHeartbeatTime is the last time this condition was updated.

- `lastTransitionTime` : `string`

LastTransitionTime is the last time the condition changed from one status to another.

- `message` : `string`

Message is a human-readable message indicating details about the last status change.

- `reason` : `string`

Reason is a brief reason for the condition's last status change.

- `status` : `string`

Status is one of True, False, Unknown.

- `type` : `string`

Type is the type of the cluster condition.

TOC

[/auth/v1/clusters](#)

`get` list clusters by rbac

Parameters

Response

ClusterList

ListMeta

Cluster

ClusterSpec

ClusterAuthInfo

ClusterAuthReference

KubernetesAPIEndpoints

ServerAddressByClientCIDR

ClusterStatus

ClusterCondition

Related APIs

API usage

Request example

Response example

Notes

Related APIs

- [Project \[v1\]](#)

API usage

This API does not use `/kubernetes/{cluster}` as a path prefix.

GET `/auth/v1/clusters`

Common query parameters:

Parameter	Type	Description
<code>labelSelector</code>	<code>string</code>	Restricts returned clusters by labels.
<code>fieldSelector</code>	<code>string</code>	Restricts returned clusters by fields, such as <code>metadata.name</code> .
<code>limit</code>	<code>integer</code>	Limits the number of returned records.
<code>continue</code>	<code>string</code>	Continue token for paginated queries.
<code>resourceVersion</code>	<code>string</code>	Constrains what resource versions the request may be served from.
<code>watch</code>	<code>boolean</code>	Watches for changes to clusters.
<code>timeoutSeconds</code>	<code>integer</code>	Timeout for list/watch requests.

Request example

```
curl -H "Authorization: Bearer ${TOKEN}" \
  "${APISERVER}/auth/v1/clusters?fieldSelector=metadata.name=${CLUSTER_NAME}"
```

Response example

```
{
  "apiVersion": "clusterregistry.k8s.io/v1alpha1",
  "kind": "ClusterList",
  "metadata": {
    "resourceVersion": "12345678",
    "continue": ""
  },
  "items": [
    {
      "metadata": {
        "name": "cluster-a"
      },
      "spec": {
        "kubernetesApiEndpoints": {
          "serverEndpoints": [
            {
              "serverAddress": "https://api.cluster-a.example.com"
            }
          ]
        }
      },
      "status": {
        "type": "Kubernetes",
        "version": "v1.30.0"
      }
    }
  ]
}
```

Notes

- This API returns clusters filtered by RBAC.
- Some sensitive fields are filtered from the response by the backend.