
[Alauda Container Platform](#) > [API References](#) > [Kubernetes APIs](#) > Etcd APIs

Etcd APIs

[EtcdCluster \[operator.etcd.io/v1alpha1\]](#)

EtcdCluster [operator.etcd.io/v1alpha1]

Description

EtcdCluster is the Schema for the etcdclusters API.

Type

object

Specification

Property	Type	Description
apiVersion	string	APIVersion defines the versioned schema of this representation of an object. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#resources

Property	Type	Description
kind	string	Kind is a string value representing the REST resource this object represents. Servers may infer this from the endpoint the client submits requests to. Cannot be updated. In CamelCase. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#types-kinds ↗
metadata	ObjectMeta	ObjectMeta is metadata that all persisted resources must have, which includes all objects users must create.
spec	object	EtcdClusterSpec defines the desired state of EtcdCluster.
status	object	EtcdClusterStatus defines the observed state of EtcdCluster.

.spec

Description

EtcdClusterSpec defines the desired state of EtcdCluster.

Type

object

Required

size version

Property	Type	Description
<code>etcdOptions</code>	<code>array</code>	etcd configuration options are passed as command line arguments to the etcd container, refer to etcd documentation for configuration options applicable for the version of etcd being used.
<code>imageRegistry</code>	<code>string</code>	ImageRegistry specifies the container registry that hosts the etcd images. If unset, it defaults to the value provided via the controller's --image-registry flag, which itself defaults to "gcr.io/etcd-development/etcd".
<code>podTemplate</code>	<code>object</code>	PodTemplate is the pod template to use for the etcd cluster.
<code>size</code>	<code>integer</code>	Size is the expected size of the etcd cluster.
<code>storageSpec</code>	<code>object</code>	StorageSpec is the name of the StorageSpec to use for the etcd cluster. If not provided, then each POD just uses the temporary storage inside the container.
<code>tls</code>	<code>object</code>	TLS is the TLS certificate configuration to use for the etcd cluster and etcd operator.
<code>version</code>	<code>string</code>	Version is the expected version of the etcd container image.

.spec.etcdOptions

Description

etcd configuration options are passed as command line arguments to the etcd container, refer to etcd documentation for configuration options applicable for the version of etcd being used.

Type

array

.spec.etcdOptions[]

Type

string

.spec.podTemplate

Description

PodTemplate is the pod template to use for the etcd cluster.

Type

object

Property	Type	Description
metadata	ObjectMeta	Metadata is the metadata to add to the pod.

.spec.storageSpec

Description

StorageSpec is the name of the StorageSpec to use for the etcd cluster. If not provided, then each POD just uses the temporary storage inside the container.

Type

`object`

Required

`volumeSizeRequest`

Property	Type	Description
<code>accessModes</code>	<code>string</code>	
<code>pvcName</code>	<code>string</code>	
<code>storageClassName</code>	<code>string</code>	
<code>volumeSizeLimit</code>		
<code>volumeSizeRequest</code>		

.spec.tls

Description

TLS is the TLS certificate configuration to use for the etcd cluster and etcd operator.

Type

`object`

Property	Type	Description
<code>provider</code>	<code>string</code>	
<code>providerCfg</code>	<code>object</code>	

.spec.tls.providerCfg

Type

`object`

Property	Type	Description
<code>autoCfg</code>	<code>object</code>	
<code>certManagerCfg</code>	<code>object</code>	

`.spec.tls.providerCfg.autoCfg`

Type

`object`

Property	Type	Description
<code>altNames</code>	<code>object</code>	AltNames contains the domain names and IP addresses that will be added to the x509 certificate SubAltNames fields. The values will be passed directly to the x509.Certificate object.
<code>caBundleSecret</code>	<code>string</code>	CABundleSecret is the expected secret name with CABundle present. It's used by each etcd POD to verify TLS communications with its peers or clients. If it isn't provided, the CA included in the secret generated by certificate provider will be used instead if present; otherwise, there is no way to verify TLS communications.
<code>commonName</code>	<code>string</code>	CommonName is the expected common name X509 certificate subject attribute. Should have a length of 64 characters or fewer to avoid generating invalid CSRs.

Property	Type	Description
<code>organizations</code>	<code>array</code>	Organization is the expected array of Organization names to be used on the Certificate.
<code>validityDuration</code>	<code>string</code>	ValidityDuration is the expected duration until which the certificate will be valid, expects in human-readable duration: 100d12h, if empty defaults to 90d

`.spec.tls.providerCfg.autoCfg.altNames`

Description

AltNames contains the domain names and IP addresses that will be added to the x509 certificate SubAltNames fields. The values will be passed directly to the x509.Certificate object.

Type

`object`

Property	Type	Description
<code>dnsNames</code>	<code>array</code>	DNSNames is the expected array of DNS subject alternative names defaults to <code>\$(POD_NAME).\$(ETCD_CLUSTER_NAME).\$(POD_NAMESPACE)</code>
<code>ipAddresses</code>	<code>array</code>	IPs is the expected array of IP address subject alternative names

`.spec.tls.providerCfg.autoCfg.altNames.dnsNames`

Description

DNSNames is the expected array of DNS subject alternative names. if empty defaults to \$(POD_NAME).\$(ETCD_CLUSTER_NAME).\$(POD_NAMESPACE).svc.cluster.local

Type`array`**.spec.tls.providerCfg.autoCfg.altNames.dnsNames[]****Type**`string`**.spec.tls.providerCfg.autoCfg.altNames.ipAddresses****Description**

IPs is the expected array of IP address subject alternative names.

Type`array`**.spec.tls.providerCfg.autoCfg.altNames.ipAddresses[]****Type**`string`**.spec.tls.providerCfg.autoCfg.organizations****Description**

Organization is the expected array of Organization names to be used on the Certificate.

Type`array`**.spec.tls.providerCfg.autoCfg.organizations[]****Type**

`string`

`.spec.tls.providerCfg.certManagerCfg`

Type

`object`

Required

`issuerKind``issuerName`

Property	Type	Description
<code>altNames</code>	<code>object</code>	AltNames contains the domain names and IP addresses that will be added to the x509 certificate SubAltNames fields. The values will be passed directly to the x509.Certificate object.
<code>caBundleSecret</code>	<code>string</code>	CABundleSecret is the expected secret name with CABundle present. It's used by each etcd POD to verify TLS communications with its peers or clients. If it isn't provided, the CA included in the secret generated by certificate provider will be used instead if present; otherwise, there is no way to verify TLS communications.
<code>commonName</code>	<code>string</code>	CommonName is the expected common name X509 certificate subject attribute. Should have a length of 64 characters or fewer to avoid generating invalid CSRs.

Property	Type	Description
<code>issuerKind</code>	<code>string</code>	IssuerKind is the expected kind of Issuer, either "ClusterIssuer" or "Issuer"
<code>issuerName</code>	<code>string</code>	IssuerName is the expected name of Issuer required to issue a certificate
<code>organizations</code>	<code>array</code>	Organization is the expected array of Organization names to be used on the Certificate.
<code>validityDuration</code>	<code>string</code>	ValidityDuration is the expected duration until which the certificate will be valid, expects in human-readable duration: 100d12h, if empty defaults to 90d

.spec.tls.providerCfg.certManagerCfg.altNames

Description

AltNames contains the domain names and IP addresses that will be added to the x509 certificate SubAltNames fields. The values will be passed directly to the x509.Certificate object.

Type

`object`

Property	Type	Description
<code>dnsNames</code>	<code>array</code>	DNSNames is the expected array of DNS subject alternative names. Defaults to \$(POD_NAME).\$(ETCD_CLUSTER_NAME).\$(POD_NAMESPACE).svc.cluster.local
<code>ipAddresses</code>	<code>array</code>	IPs is the expected array of IP address subject alternative names.

`.spec.tls.providerCfg.certManagerCfg.altNames.dnsNames`

Description

DNSNames is the expected array of DNS subject alternative names. if empty defaults to \$(POD_NAME).\$(ETCD_CLUSTER_NAME).\$(POD_NAMESPACE).svc.cluster.local

Type

`array`

`.spec.tls.providerCfg.certManagerCfg.altNames.dnsNames[]`

Type

`string`

`.spec.tls.providerCfg.certManagerCfg.altNames.ipAddresses`

Description

IPs is the expected array of IP address subject alternative names.

Type

`array`

.spec.tls.providerCfg.certManagerCfg.altNames.ipAddresses[]

Type

`string`

.spec.tls.providerCfg.certManagerCfg.organizations

Description

Organization is the expected array of Organization names to be used on the Certificate.

Type

`array`

.spec.tls.providerCfg.certManagerCfg.organizations[]

Type

`string`

.status

Description

EtcdClusterStatus defines the observed state of EtcdCluster.

Type

`object`

API Endpoints

The following API endpoints are available:

- `/apis/operator.etcd.io/v1alpha1/namespaces/{namespace}/etcdclusters`
 - **DELETE** : delete collection of EtcdCluster
 - **GET** : list objects of kind EtcdCluster
 - **POST** : create a new EtcdCluster
- `/apis/operator.etcd.io/v1alpha1/namespaces/{namespace}/etcdclusters/{name}`
 - **DELETE** : delete the specified EtcdCluster
 - **GET** : read the specified EtcdCluster
 - **PATCH** : partially update the specified EtcdCluster
 - **PUT** : replace the specified EtcdCluster
- `/apis/operator.etcd.io/v1alpha1/namespaces/{namespace}/etcdclusters/{name}/status`
 - **GET** : read status of the specified EtcdCluster
 - **PATCH** : partially update status of the specified EtcdCluster
 - **PUT** : replace status of the specified EtcdCluster

`/apis/operator.etcd.io/v1alpha1/namespaces/{namespace}/etcdclusters`

HTTP method

DELETE

Description

delete collection of EtcdCluster

HTTP responses

HTTP code	Response body
200 - OK	Status schema
401 - Unauthorized	Empty

HTTP method

GET

Description

list objects of kind EtcdCluster

HTTP responses

HTTP code	Response body
200 - OK	<code>EtcdClusterList</code> schema
401 - Unauthorized	Empty

HTTP method

POST

Description

create a new EtcdCluster

Query parameters

Parameter	Type	Description
<code>dryRun</code>	<code>string</code>	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed
<code>fieldValidation</code>	<code>string</code>	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields.

Parameter	Type	Description
		This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Body parameters

Parameter	Type	Description
body	EtcdCluster schema	application/json formatted

HTTP responses

HTTP code	Response body
200 - OK	EtcdCluster schema
201 - Created	EtcdCluster schema
202 - Accepted	EtcdCluster schema
401 - Unauthorized	Empty

/apis/operator.etcd.io/v1alpha1/namespaces/{namespace}/etcdclusters/{name}

HTTP method

DELETE

Description

delete the specified EtcdCluster

Query parameters

Parameter	Type	Description
<code>dryRun</code>	<code>string</code>	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed

HTTP responses

HTTP code	Response body
200 - OK	<code>Status</code> schema
202 - Accepted	<code>Status</code> schema
401 - Unauthorized	Empty

HTTP method

`GET`

Description

read the specified EtcdCluster

HTTP responses

HTTP code	Response body
200 - OK	<code>EtcdCluster</code> schema
401 - Unauthorized	Empty

HTTP method

`PATCH`

Description

partially update the specified EtcdCluster

Query parameters

Parameter	Type	Description
<code>dryRun</code>	<code>string</code>	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed
<code>fieldValidation</code>	<code>string</code>	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

HTTP responses

HTTP code	Response body
200 - OK	<code>EtcdCluster</code> schema
401 - Unauthorized	Empty

HTTP method

`PUT`

Description

replace the specified EtcdCluster

Query parameters

Parameter	Type	Description
<code>dryRun</code>	<code>string</code>	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed
<code>fieldValidation</code>	<code>string</code>	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Body parameters

Parameter	Type	Description
<code>body</code>	<code>EtcdCluster</code> schema	<code>application/json</code> formatted

HTTP responses

HTTP code	Response body
200 - OK	<code>EtcdCluster</code> schema

HTTP code	Response body
201 - Created	<code>EtcdCluster</code> schema
401 - Unauthorized	Empty

/apis/operator.etcd.io/v1alpha1/namespaces/{namespace}/etcdclusters/{name}/status

HTTP method

`GET`

Description

read status of the specified EtcdCluster

HTTP responses

HTTP code	Response body
200 - OK	<code>EtcdCluster</code> schema
401 - Unauthorized	Empty

HTTP method

`PATCH`

Description

partially update status of the specified EtcdCluster

Query parameters

Parameter	Type	Description
<code>dryRun</code>	<code>string</code>	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed

Parameter	Type	Description
<code>fieldValidation</code>	<code>string</code>	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

HTTP responses

HTTP code	Response body
200 - OK	<code>EtcdCluster</code> schema
401 - Unauthorized	Empty

HTTP method

`PUT`

Description

replace status of the specified EtcdCluster

Query parameters

Parameter	Type	Description
<code>dryRun</code>	<code>string</code>	When present, indicates that modifications should not be persisted. An invalid or unrecognized dryRun

Parameter	Type	Description
		directive will result in an error response and no further processing of the request. Valid values are: - All: all dry run stages will be processed
<code>fieldValidation</code>	<code>string</code>	fieldValidation instructs the server on how to handle objects in the request (POST/PUT/PATCH) containing unknown or duplicate fields. Valid values are: - Ignore: This will ignore any unknown fields that are silently dropped from the object, and will ignore all but the last duplicate field that the decoder encounters. This is the default behavior prior to v1.23. - Warn: This will send a warning via the standard warning response header for each unknown field that is dropped from the object, and for each duplicate field that is encountered. The request will still succeed if there are no other errors, and will only persist the last of any duplicate fields. This is the default in v1.23+ - Strict: This will fail the request with a BadRequest error if any unknown fields would be dropped from the object, or if any duplicate fields are present. The error returned from the server will contain all unknown and duplicate fields encountered.

Body parameters

Parameter	Type	Description
<code>body</code>	<code>EtcdCluster</code> schema	<code>application/json</code> formatted

HTTP responses

HTTP code	Response body
200 - OK	<code>EtcdCluster</code> schema
201 - Created	<code>EtcdCluster</code> schema
401 - Unauthorized	Empty

